Cooling

ALC 100 GLASS

+2...+10°C



Standard equipment:

- RAL 9016 coated exterior
- Interior made of AISI 304 acid-resistant steel
- 70 mm insulation
- Environmentally friendly refrigerant
- Glass door with replaceable seal
- Mechanical door lock
- Automatic door closing system`
- Right hinged door
- Electronic temperature controller with digital display with the possibility of changing the temperature setting every 0.1k
- Visual and sound alarm for high and low temperature
- Open door alarm
- Dirty condenser coil alarm
- Faulty temperature sensor alarm
- External alarm output potential-free contact
- Auto defrost and condensation evaporation
- Antifreeze system
- Shelf guides / horizontal supports
- 2 coated wire shelves
- Adjustable shelf position
- Access port Ø10mm
- Adjustable feet
- LED lighting


Optional equipment:

- Alarm backup battery
- Power failure alarm
- Temperature sensor
- Change of standard temperature range
- Additional access port in the wall Ø10mm
- Glycol container
- 4 swivel casters, 2 of which have brakes
- Additional shelf guides / horizontal supports
- Additional shelves (coated wire, stainless steel wire)
- Left hinged door
- External housing made of acid-resistant AISI 304 steel

APOLLO
Laboratory Technology

ALC 100 GLASS

- Environmentally friendly refrigerant
- Antifreeze system
- Access port Ø10mm
- LED lighting



Technical specifications:

	Width	Depth	Height
External dimensions [mm]	650	645	853
Internal dimensions [mm]	510	356/172	625
Cooling unit type	Internal		
Cooling type	Dynamic		
Gross capacity	90 [liters]		
Net capacity	85 [liters]		
Weight	90 [kg]		
Max. load	60 [kg]		
Number of shelves	2		
Number of guides / horizontal supports	8		
Max. shelf load	25 [kg]		
Temperature range	+2...+10 [°C]		
Ambient conditions	+25 [°C] op 60% HR		
Refrigerant	R600a		
Power	230/50 [V/Hz]		
Number of external doors	1		
Daily energy consumption	2.7 [kWh/24h]		
Noise level	51 [db]		
Power rating	230 [W]		
Rated current	1.0 [A]		

APOLLO
Laboratory Technology